

# Surface T/S Data RV "Heincke"

## HE527

### Data Processing Report

#### Contents

<b>1</b>	<b>Introduction</b>	<b>2</b>
<b>2</b>	<b>Workflow</b>	<b>2</b>
<b>3</b>	<b>Cruise details</b>	<b>3</b>
<b>4</b>	<b>Sensor</b>	<b>3</b>
<b>5</b>	<b>Processing Report</b>	<b>4</b>

#### Contact:

Gerd Rohardt

Alfred-Wegener-Institute

Am Handelshafen 12, D-27570 Bremerhaven, GERMANY

Mail: [info@awi.de](mailto:info@awi.de)

#### Processing Agency:

FIELAX

Schleusenstr. 14, D-27568 Bremerhaven, GERMANY

Mail: [info@fielax.de](mailto:info@fielax.de)

Ref.: HE527_TSG.pdf	Vers.: 1.1	Date: 2019/06/06	Status: final
---------------------	------------	------------------	---------------

**Report History**

Version No.	Author	Date	Comments or Changes
Vers. 1	FIELAX GmbH	11.04.2016	first edition
Vers. 1.1	FIELAX GmbH	27.02.2018	Flow Rate Filter added; minor text changes

# 1 Introduction

This report describes the processing of raw data acquired by the thermosalinograph on board RV "Heincke" during expedition HE527 to receive cleaned up and drift corrected salinity data.

## 2 Workflow

The different steps of processing are visualized in Figure 1. Unvalidated data of conductivity sensor, internal and external temperature are extracted from the DAVIS SHIP data base (<https://dship.awi.de>) in a 1-second interval. The salinity was calculated using conductivity and internal temperature by applying the Practical Salinity Scale 1978 (PSS-78).

As a first step, a basic cleanup was performed to remove missing or flagged data. Then, too low flow rates are taken as indicator for an improper usage of the thermosalinograph. Since the salinity measurements in coastal areas (e.g. rivers and ports) are less reliable, measurements in a buffer of 2 nautical miles (NM) along the coast are filtered. In the Norwegian area (fjords) the buffer is set to 200 meters (0.108 NM). After the exclusion of data outside the speed interval of 0.5 kn to 15 kn, the salinity is driftcorrected with lab calibration data. In the next processing step, data with differences between external and internal temperature sensor  $> 5$  K are removed. After despiking, a visual screening is performed to enhance the data quality. Then, the temporal resolution is reduced to 5-minutes-means. In the last step, the 5-minute-means of salinity and external temperature are exported.




Figure 1: Workflow of TSG data processing

### 3 Cruise details

Vessel name      RV "Heincke"  
 Cruise name      HE527  
 Cruise start      19.03.2019 Bremerhaven  
 Cruise end        31.03.2019 Bremerhaven  
 Cruise duration   13 days

### 4 Sensor

Thermosalinograph:    Seabird SEACAT SBE21 (SN: 3334)  
 External Temperature:   SBE38




Figure 2: Cruisemap of HE527.

## 5 Processing Report

### Database Extraction

Data source	DSHIP database (dship.awi.de)
Exported values	1049401
First dataset	2019-03-19T07:30:00 UTC
Last dataset	2019-03-31T11:00:00 UTC

### Automatic Validation

The following thresholds were applied for the automatic flagging of the data:

Min. flow rate	Minimum 2.5
Min. speed	Minimum 0.5 kn between two datapoints.
Max. speed	Maximum 40 kn between two datapoints.
GeoBuffer	0.1080 NM around Norway, 2 NM anywhere else
Temperature	Maximum T-difference of 5 K.

### Flagging result

Filter	Data left (abs.)	Data left (rel.)	Data removed (abs.)	Data removed (rel.)
Raw data	1049401	100 %	—	—
Basic	287053	27.35 %	762348	72.65 %
Flow rate	244662	23.31 %	804739	76.69 %
Geo	234728	22.37 %	814673	77.63 %
Speed	217161	20.69 %	832240	79.31 %
Temperature	217143	20.69 %	832258	79.31 %
Despike	217142	20.69 %	832259	79.31 %
Manual	217053	20.68 %	832348	79.32 %
5-min-Mean	2726	0.26 %	1046675	99.74 %

### Sensordrift

Last calibration	06.03.2018
Current calibration	16.05.2019
Start of deployment	14.11.2018
End of deployment	24.04.2019
Scaled drift	-1.8335e-004 [PSU/month]
Minimal offset	7.5539e-004 [PSU]
Maximal offset	8.2861e-004 [PSU]

### Comments

—

## Process evolution




Figure 3: Raw salinity data.




Figure 4: Salinity after basic filter.




Figure 5: Salinity after flow rate filter.




Figure 6: Salinity after geofilter.




Figure 7: Salinity after speed filter.




Figure 8: Salinity after temperature filter.




Figure 9: Salinity after despiking.




Figure 10: Salinity after manual filter.




Figure 11: Salinity in 5-min-mean values.



## Result file

Text File (HE527\_surf\_oce.tab):

The format is a plain text (tab-delimited values) file.

Column separator	Tabulator "\t"
Column 1	Date and time expressed according to ISO 8601
Column 2	Latitude in decimal format, unit degree
Column 3	Longitude in decimal format, unit degree
Column 4	Depth below water surface, unit meter
Column 5	Temperature, unit degree
Column 6	Salinity, unit PSU

Processing Report (HE527\_TSG.pdf):

This PDF document.